

POLY-SOLV POLYMER SOLVENT

**A UNIQUE BLEND OF ALKALIES, PENETRANTS, EMULSIFIERS AND
MULTI-COMPONENT SURFACTANTS
(CONTAINS NO CHLORINATED SOLVENTS, OR ACIDS)**

For fast, powerful removal of sticky polymer residues

DESCRIPTION

Poly-Solv is a concentrated polymer solvent formulated to rapidly remove sticky polymer residues from belt press belts, polymer make-up tanks, floors, stairs—anyplace where polymer residues present a problem. Poly-Solv rapidly breaks the cohesive bond between the polymer molecules and the surfaces to which they adhere so that they can be rinsed away with water.

DIRECTIONS FOR USE

Use approximately 1 part poly-solv to 3 parts water in spray-type applicator or pressure washer.

Belt Presses/Thickeners- Turn off the water rinse to the press. Slow belt speed and thoroughly spray belt with Poly-Solv while belt is moving. Wait 5 minutes. Turn on belt press water rinse for a completely clean, unblinded belt.

Spills or flat surfaces- Use spray type applicator. Apply liberally to the surface and allow to remain 5 to 15 minutes. Agitate with a stiff brush to completely break up the film, then flush away with water. Hard, dry, polymer residues may require a longer contact time and/or a second application to remove polymer build-up.

Feed Equipment- Flush lines with water to remove gross polymer residues. Recirculate Poly-Solv until lines are free flowing. To clean polymer make-up tanks-add **Poly-Solv** and water to tank, let sit for as long as possible, then flush clean with water.



26808 County Rte 3, Plessis, NY 13675 (315) 482-3787

email: stewardell@cleanwaters.us

www.cleanwaters.us